

JW-D60N


N-type Bifacial High Efficiency Mono Silicon Double Glass Module

330-355W

Cell Type



12BB



355W

Maximum Power Output

21.34%

Maximum Module Efficiency

0~+5W

Power Output Guarantee



Additional Power Generation Gain

At least 30-year product life, more than 10%- 30% additional power gain comparing with conventional module



ZERO LID (Light Induced Degradation)

N-type solar cell has no LID naturally, can increase power generation



Lower LCOE

High power and 1500V system voltage, saving BOS cost



Better Weak Illumination Response

Wide spectral response, higher power output even under low-light settings like smog or cloudy days



Better Temperature Coefficient

Higher power generation under working conditions, thanks to passivating contact cell technology




Wider Applicability

BIPV, vertical installation, snowfield, high-humid area, windy and dusty area

Jolywood Delivers Reliable Performance Over Time

- Leader of n-type bifacial technology
- Fully automatic facility and world-class technology
- Long term reliability tests
- 100% EL inspection ensuring defect-free modules

Linear Performance Warranty



12 Years Product Material & Workmanship 30 Years Linear Performance Warranty

Additional Insurance Backed by Munich Re



JW-D60N Series | N-type Bifacial High Efficiency Mono Silicon Double Glass Module

Electrical Properties | STC*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (Pmax) (W)	330	335	340	345	350	355
MPP Voltage (Vmp) (V)	34.4	34.7	35.1	35.4	35.7	35.9
MPP Current (Imp) (A)	9.60	9.66	9.70	9.75	9.81	9.89
Open Circuit Voltage (Voc) (V)	41.2	41.5	41.8	42.1	42.4	42.6
Short Circuit Current (Isc) (A)	10.07	10.12	10.17	10.22	10.28	10.36
Module Efficiency (%)	19.84	20.14	20.44	20.74	21.04	21.34

*STC: Irradiance 1000 W/m², Cell Temperature 25°C, AM1.5
The data above is for reference only and the actual data is in accordance with the practical testing

Electrical Properties | NOCT*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (Pmax) (W)	250	253	257	261	265	269
MPP Voltage (Vmp) (V)	32.3	32.5	32.9	33.2	33.5	33.7
MPP Current (Imp) (A)	7.74	7.79	7.82	7.86	7.91	7.97
Open Circuit Voltage (Voc) (V)	39.4	39.7	40.0	40.2	40.5	40.7
Short Circuit Current (Isc) (A)	8.12	8.16	8.20	8.24	8.29	8.35

*NOCT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s

Operating Properties

Operating Temperature (°C)	-40°C~+85°C
Maximum System Voltage (V)	1500V (IEC)
Maximum Series Fuse Rating(A)	20
Power Tolerance	0~+5W
Bifaciality*	80%

*Bifaciality=Pmaxrear (STC) /Pmaxfront (STC) , Bifaciality tolerance:±5%

Temperature Coefficient

Temperature Coefficient of Pmax*	-0.320%/°C
Temperature Coefficient of Voc	-0.260%/°C
Temperature Coefficient of Isc	+0.046%/°C
Nominal Operating Cell Temperature (NOCT)	42±2°C

*Temperature Coefficient of Pmax±0.03%/°C

Mechanical Properties


Cell Type	158.75mm*158.75mm
Number of Cells	60pcs(6*10)
Dimension	1670mm*996mm*30mm
Weight	21.5Kg
Front /Rear Glass*	2.0mm/2.0mm
Frame	Anodized Aluminium
Junction Box	IP68 (3 diodes)
Length of Cable*	4.0mm ² , 300mm
Connector	MC4 Compatible

*Heat strengthened glass
*Cable length can be customized




With Different Power Generation Gain (regarding 340W as an example)

Power Gain (%)	Peak Power (Pmax) (W)	MPP Voltage (Vmp) (V)	MPP Current (Imp) (A)	Open Circuit Voltage (Voc) (V)	Short Circuit Current (Isc) (A)
10	367	35.1	10.46	41.8	10.96
15	381	35.1	10.83	41.8	11.36
20	394	35.2	11.21	41.9	11.76
25	408	35.2	11.59	41.9	12.15
30	422	35.2	11.97	41.9	12.55

Engineering Drawing (unit : mm)



Characteristic Curves | D60N-340



Packaging Configuration

Packing Type	20'GP	40'GP	40'HQ
Piece/Pallet		35	
Pallet/Container	6	13	26
Piece/Container	210	455	910

*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Jolywood (Taizhou) Solar Technology Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

